



Conveyor Guide Company Limited

Bucket Belt Solid Woven Type Specification

Website : www.conveyorguide.co.th

Email : banyad@conveyorguide.co.th

Contact Person : Banyad Jaiman (NEW)

E-Mail : banyad@conveyorguide.co.th

Mobile : 083-131-86 44

Bucket Conveyor Belt Solid Woven Type Specification

Conveyor Belt Type		360	480	680	880	1080	1600	1800	2000	2500	3100	3500
Minimum Tensile Strength (N/mm.)	Warp	360	480	680	880	1080	1600	1800	2000	2500	3150	3400
	Weft	200	220	250	300	320	350	450	450	450	450	500
Minimum Elongation at Break (%)	Warp	16										
	Weft	20										
Cover Elongation @ Break %		400										
Thickness (mm.)		3.4	4.1	5.4	6.9	8.8	9.5	10	10.5	12.5	17	20
Cover Grade	PVC	1.5+1.5	1.5+1.5	2+1.5	2+2	3+2	3+2	3+2	3+2	3+2	3+2	3+2
Min. Pulley Dia. (mm.)		100	100	150	250	350	800	800	1000	1200	1500	-
10 % Elongation @ Rated Load		0.6					0.7					

Solid Woven Carcass

